



# System 4

Walkways, escape routes and lay down areas

## System 4: Decks

Pre-qualification is required

Product	DFT (µm)
Hempadur Spray-Guard 35493	3000
<b>Total</b>	<b>3000</b>

Product	DFT (µm)
Hempadur Spray-Guard 35493	1500
Hempadur Spray-Guard 35493	1500
<b>Total</b>	<b>3000</b>

Product	DFT (µm)
Hempadur 15590	20 <sup>1</sup>
Hempadur Spray-Guard 35493	3000
<b>Total</b>	<b>3020*</b>

\*According to ISO 19840

Note 1: The use of Hempadur 15590 is optional.

Note 2: The coating schemes for System 4 relate to walkways, escape routes and laydown areas. Coating schemes pre-qualified according to NORSOK M-501 System 1 may be used for other deck areas with the addition of a non-skid aggregate (Hempel 67500). Hempel's Anti-slint 67500 may be added to the systems to provide non-slip properties. This note applies to all of the above systems.

For advice on regional product availability and additional schemes, please contact your local Hempel representative or email [protective@hempel.com](mailto:protective@hempel.com)

**Hempel A/S**  
 Lundtoftegaardsvej 91, 2800 Kgs. Lyngby, Denmark  
 Tel: +45 4593 3800 Email: [norsok@hempel.com](mailto:norsok@hempel.com)  
[norsok.hempel.com](http://norsok.hempel.com)